

Ficient Int'l Co., Limited

Address: 3-1-1701 Chuan Shui Yuan, Sui Jiang Rd, Hexi Dist., Tianjin 300221 China

Tel/Fax: +86 22 28287095 Cell: +86 13820587585

Email: ficient2012@gmail.com Skype: ficient2012

Page | 20

Product Catalog

RG59+Power



>> BASIC CONSTRUCTION

Component		RG59+Power
CONDUCTOR	MATERIAL	CCS/BC
	Nom.Dia.	0.80 ± 0.01mm
DIELECTRIC	MATERIAL	Foam PE
	Nom.Dia.	3.70 ± 0.10mm
SHIELD	MATERIAL	BC/CCA Braid
	COVERAGE	95%
JACKET	MATERIAL	PVC
	Nom.Dia.	6.0 ± 0.10mm
Power Pair	MATERIAL	BC
	Nom.Dia.	16/24x0.2mm+1.8mm PE/PVC

>> BASIC CHARACTERISTICS

Nominal Impedance(ohm)		75 ± 3
Nominal Velocity of propagation(%)		83%
Nominal Capacitance(pf/m)		53.4
Attenuation [68° F(20°C)]	Frequency(MHZ)	Attenuation (dB/100m)
	10	3.0
	50	6.23
	100	8.53
	200	12.1
	400	17.5
	700	24.0
	900	27.3
	1000	29.0

