

Ficient Int'l Co., Limited

Address: 3-1-1701 Chuan Shui Yuan, Sui Jiang Rd, Hexi Dist., Tianjin 300221 China

Tel/Fax: +86 22 28287095

Cell: +86 13820587585

Email: ficient2012@gmail.com

Skype: ficient2012

Website: www.ficientcable.com

Page | 1

Product Catalog

Description

Replacement 12V DC Cable for Waeco: CFX-35, 40, 50, 65, 65DZ - CF-25 VERA, CF-35AC VERB, CF-40AC VERB, CF-50AC VERB, CF-60AC VERB model fridges.

Specification

Connector Type	Type A, type B, type C(mini), type D(micro)
Conductor	Oxygen-free Pure Copper (OFC), 28AWG + 28AWG
Wire gauge	AWG22, AWG24, AWG28, AWG30
Cable OD	3.0mm, 3.5mm, 3.8mm, 4.5mm, 5.5mm, 6.0mm
Length	1ft - 50ft (Optional)
Shielding	Al-foil & 16*4/0.12mm Tinned annealed copper Braid
Transfer speed	USB 2.0 up to 480Mbps, USB 3.0 up to 5Gbps
Insulation	HD-PE (White & Green) & SR-PVC(Red & Black)
Power Supply	Max+5V DC 500Ma from connected host USB
Color	White / Black / Red / Blue / Green /Orange (Optional)
Voltage resistance	300V DC, 60Hz 0.02 second
Contact resistance	Max 3Mohm
Application	Computer, Digital Camera, USB Hub, Cell phone for HTC, Samsung, etc

Electrical Test

1. 100% open & short test
2. Hi-Pot: DC 300V 10ms
3. Insulation resistance: 0.01OHM Max/300V Min
4. Contact resistance: 0.01 OHM Max
5. Shield up to 65% braid
6. Working temperature: -25°C~+85°C

